

LUKOIL ATF

Product number: 583315

High performance semi-synthetic automatic transmission fluid

APPROVALS

BELAZ
MAN 339 Typ Z1/ L1/ V1
Voith H55.6335.XX
ZF TE-ML 04D/ 14A (ZF001146)

MEETS REQUIREMENTS

Allison C-4
Caterpillar TO-2
GM Dexron® II-D/ III-G
MAN 339 Typ D/ F
MB 236.1, 236.6
RBAS TE-ML 09
Volvo 97340/ 97341
ZF TE-ML 11A/ 11B/ 17C

PRODUCT DESCRIPTION

LUKOIL ATF is a high technology universal semi-synthetic automatic transmission fluid de-signed for both passenger cars and heavy duty truck applications.

LUKOIL ATF delivers high viscosity index performance for a wide temperature range, providing low temperature fluidity.

LUKOIL ATF offers excellent corrosion and wear protection, good antifoaming properties, thermal and oxidation stability.

LUKOIL ATF has been designed to meet and exceed requirements of the world original equipment manufacturers.

APPLICATION

LUKOIL ATF is recommended for automatic transmission systems of both passenger cars and on- and off-highway trucks where Dexron® III G products are specified.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL ATF
Density at 15 °C	kg/m ³	DIN 51575	862
Flash Point COC	°C	ISO 2592	205
Viscosity class	---	ISO VG	32
Viscosity at 40°C	mm ² /s	DIN 51562/T1	36,7
Viscosity at 100°C	mm ² /s	DIN 51562/T1	7,44
Viscosity index	---	DIN ISO 2909	172
Pourpoint	°C	DIN ISO 3016	< -56

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

Mar. 21, 19, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe GmbH
 Uferstrasse 8
 1220 Vienna, Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of::

