

LUKOIL TRANSMISSION SLY 75W-90

fully synthetic gear oil developed for car gearbox transmissions and transaxle systems

APPROVALS

MEETS REQUIREMENTS

API GL-4+
VW 501.50

PRODUCT DESCRIPTION

LUKOIL TRANSMISSION SLY 75W-90 is fully synthetic gear oil developed for car gearbox transmissions and transaxle systems. It ensures optimum gear change comfort even at low winter temperatures.

LUKOIL TRANSMISSION SLY 75W-90 shows excellent aging stability and thus longest service life for transmissions.

LUKOIL TRANSMISSION SLY 75W-90 modern high performance anti-wear and anti-corrosion additives provide a stable lubricant film and best extreme pressure-stability.

LUKOIL TRANSMISSION SLY 75W-90 has low viscosity temperature dependency and a low pour point which allows easy shifting also at very low temperatures.

APPLICATION

LUKOIL TRANSMISSION SLY 75W-90 is fully synthetic gear oil especially designed for modern manual transmissions and transaxle-systems of passenger cars and LDTs. Based on synthetic oils it provides easy shifting even at very low temperatures and prevents from wear also at highest thermal stress. Please refer to the manufacturer's manuals!

TYPICAL TEST DATA

Product number: 583240

PROPERTY	Units	Test methods	LUKOIL TRANSMISSION SLY 75W-90
Density at 15 °C	kg/m ³	DIN 51575	845
Flash Point COC	°C	ISO 2592	180
Viscosity class	---	SAE J 306	75W-90
Viscosity at 40°C	mm ² /s	DIN 51562/T1	88
Viscosity at 100°C	mm ² /s	DIN 51562/T1	14,6
Viscosity Index	---	DIN ISO 2909	173
Pourpoint	°C	DIN ISO 3016	<-51

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"