

Teboil Silver Classic GT-S 20W-50

DESCRIPTION OF THE PRODUCT

Silver Classic GT-S 20W-50 is high performance motor oil for classic vehicles. It is made of thick mineral base oils and has very powerful additive system to protect the engine against wear, even highly tuned-up motors and engines running hotter than normal. Seal swelling additives helps to prevent oil leaks. In addition it is a great choice for air-cooled motors and motorcycles with wet clutch and their transmissions.



USE, BENEFITS AND FEATURES

- Thick base oil and powerful anti-wear system protects the engine reliably against wear
- Great choice for hot running air-cooled engines
- Seal swelling additives helps to prevent oil leaks
- Suitable for motorcycles and their transmissions

SPECIFICATIONS

- API SH, SG/CF
- JASO MA

TYPICAL PHYSICAL CHARACTERISTICS

Silver Classic GT-S	20W-50	Unit	Method
Density 20 °C	888	kg/m ³	ASTM D 4052
Viscosity 40 °C	158	mm ² /s	ASTM D 445
Viscosity 100 °C	17,5	mm ² /s	ASTM D 445
CCS Viscosity -15 °C	6800	mPa.s	ASTM D 5293
Viscosity-index	120		ASTM D 2270
Flash point	235	°C	ASTM D 92
Pour point	-28	°C	ASTM D 97

HEALTH, SAFETY AND ENVIRONMENT: The product is not harmful for health when handled with care. Safety datasheet is available from : <http://www.teboil.fi/tuotteet/voiteluaineet/kayttoturvallisuustiedotteet1/> Do not release into the ground, water or sewer system. Take care of the used oil and the package. STORAGING: Storage in original packages in dry, cool and well ventilated place. Protect from direct sunlight. Keep the package closed until use.

Technical data is based on approximate measures. Due to continual product research and development, the information contained here is subjected to change without notification.

